

Miniature circuit-breaker >N< 400V, 3 kA, 2-pole, C 4A

Versiyon		
ürün marka adı	SENTRON	
ürün modeli	hat koruma şalteri 5SQ	
Genel teknik veriler		
kutup sayısı	2	
tetikleme karakteristiği sınıfı	C	
aşırı gerilim kategorisi	3	
kirlilik derecesi	3	
gerilim türü / işletim gerilimi	AC/DC	
Besleme gerilimi		
besleme gerilimi / AC'de / anma değeri	400 V	
Koruma sınıfı		
IP koruma türü	IP20	
Anahtarlama kapasitesi		
anahtarlama akım durumu		
• EN 60898 uyarınca / anma değeri	3 kA	
enerji sınırlama sınıfı	3	
Elektrik		
işletim akımı		
• 30 °C'de / anma değeri	4 A	
• 40 °C'de / anma değeri	3,7 A	
• 45 °C'de / anma değeri	3,58 A	
• 50 °C'de / anma değeri	3,48 A	
• 55 °C'de / anma değeri	3,34 A	
• 60 °C'de / anma değeri	3,2 A	
• AC'de / anma değeri	4 A	
Ürün Detayı		
ürün bileşeni / birlikte devreye giren nötr iletken	Evet	
ürün ilavesi / takılabilir / ilave tertibatlar	Hayır	
Mekanik Tasarım		
montaj derinliği	55 mm	
en birimi sayısı	2	
General Product Approval	Declaration of Conformity	other



EG-Konf.

[Miscellaneous](#)

Diğer bilgiler

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/tr/tr/Catalog/product?mlfb=5SQ2270-2YA04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/tr/ps/5SQ2270-2YA04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SQ2270-2YA04

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



