



expansion module PROFIBUS DP plug-in, for 7KM PAC3200 / 3220 4200 / 3VA COM100 / 800

Versiyon			
ürün marka adı	SETRON		
ürün tanımı	PROFIBUS DP genişletme modülü		
gerilim beslemesi türü	PAC 3200 / PAC4200 / COM100 / 800 üzerinden		
Genel teknik veriler			
MTBF	141,1 y		
potansiyel ayırım	Maks. izolasyon voltajı: 500V AC		
referans işareti / DIN 40719 uyarınca genişletilmiş IEC 204-2 uyarınca / IEC 750 uyarınca	P		
kirillik derecesi	IEC 61131 uyarınca 2		
Koruma sınıfı			
IP koruma türü	IP20		
UL 94 uyarınca yanma sınıfı	V 0		
kullanma uygunluğu	Hayır		
• reaktif güç ölçer			
Bağlantılar			
elektrik bağlantısı modeli	IEC 61158 uyarınca 9 kutuplu D alt fiş		
Mekanik Tasarım			
yükseklik	63 mm		
genişlik	43 mm		
derinlik	22 mm		
sabitlenme türü	takçıkara		
Çevresel koşullar			
ortam sıcaklığı / işletim sırasında			
• minimum	-5 °C		
• maksimum	55 °C		
ortam sıcaklığı / depolama sırasında			
• minimum	-25 °C		
• maksimum	70 °C		
Sertifikalar			
referans işareti / DIN EN 61346-2 uyarınca	P		
General Product Approval	EMC	Declaration of Conformity	other

[KC](#)



[UK Declaration of Conformity](#)



[Miscellaneous](#)



Diğer bilgiler

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/tr/tr/Catalog/product?mlfb=7KM9300-0AB01-0AA0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/tr/ps/7KM9300-0AB01-0AA0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=7KM9300-0AB01-0AA0

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



